

RONCO Item No : **6313**

Brand Name : 

Description : **Industrial 95% Efficiency Respirator, Vertical Folded**
Made in Canada

Material : Non-woven Polypropylene and polyethylene

Colour : White

- Characteristics :
- Particulate Filter Efficiency in accordance with Health Canada and NIOSH 42 CFR Part 84 (TEB-APR-STP-0059) evaluation: ≥95%
 - Breathing resistance/Differential Pressure:
 - a. Inhalation: <35 mmH₂O (343.2 Pa);
 - b. Exhalation: <25 mmH₂O (245.2 Pa)
 - Bacterial Filtration Efficiency (ASTM F2101-19): 100% BFE
 - Ability to withstand 10 N (0.98 kgf) at connection points of each headstrap



Specification :

Item number	6313
Inner Layer Material	Spunbond Polypropylene (pp), 30 gsm
Filter Media	2× layers polypropylene (pp) meltblown, 25gsm
Outer Layer	Spunbond polypropylene (pp), 50 gsm
Supportive layer	Hot-wind non-woven polypropylene (PP) and polyethylene (PE) 45 gsm
Adjustable Nose Clip	Double wire laminated – 92-97 mm × 5mm
Nose foam	Latex-free biocompatible foam, 150 mm × 25 mm
Elastic Head band	Latex-free elastic – width 6.0 mm
Upper strap	220-235 mm
Lower strap	200-210 mm

Packaging : 6313 - 30 masks x 6 bags = 180 masks per case

- Product Features :
- The lightweight, vertical folded design of the respirator provides reliable, and convenient worker respiratory protection especially in the industrial environment
 - Individual automated packaging helps protect the respirator from contamination before use
 - Compatible with a variety of eyewear
 - Conforms to eye and nose contours of the face ensuring more room for eyewear
 - Adjustable noseclip with soft and comfortable fog-reducing foam
 - This respirator contains no components made from natural rubber latex
 - High-quality noseclip ensures proper fit to all facial contours
 - Headstraps are 100% latex-free to minimize risks of allergic reactions
 - One Size Fits All

- Recommended Applications :
- Airbone Biological Particles
 - Assembly & Mechanical
 - Foundry Operation
 - Petrochemical Manufacturing
 - Dry Chemical Handling
 - Paint Preparation
 - Composite Finishing
 - Sanding
 - Bagging
 - Cleaning
 - Grinding

- Recommended Industries :
- Commercial Buildings
 - Design & Constructions
 - General Manufacturing
 - Construction
 - Heavy Infrastructure
 - Mining, Oil & Gas
 - Food Safety
 - Transportation
 - Food Processing

Storage & Handling : Store in original packaging in a cool, dry and well-ventilated area, away from dust, direct sunlight, moisture and excessive heat (-20 to +30°C (-4 to +86°F)). Avoid direct contact with the used mask. Put it in a plastic bag and discard used masks into a proper lidded trash bin.

Instructions & Restrictions For Use:

- Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging.
- This product is for single use and should be discarded after each use or a maximum of 8 hours of continuous use.
- Do not use in atmospheres containing less than 19.5% oxygen.
- Do not use in atmospheres immediately dangerous to life or health (IDLH).
- Do not exceed maximum use concentrations established by regulatory standards.
- Failure to properly use and maintain this product could result in injury or death.
- All approved respirators shall be selected, fitted, used and maintained in accordance with OSHA, CSA and other applicable regulations. This respirator does not have any replacement parts.
- This respirator helps protect against certain particulate contaminants but does not eliminate exposure to or the risk of contracting any disease or infection.
- Misuse may result in sickness or death.